## Government of West Bengal Office of the Commissioner of Police 18, Lalbazar Street, Kolkata-700 001.

No. T-282/Gen/24-25

Date - 26.12.2024

### NOTICE INVITING TENDER

Sealed tenders in printed form are invited for the following works from eligible tenderers as per particulars given below:

1. Name of work : Repairing of ceiling & wall of kitchen, bathroom, bedroom & dining room, door replacement, window glasses & inside paintng of OC's chamber & OC's Rest Room of Tala PS, Kolkata.

(Details in ANNEXURE-A)

2. Eligibility : All bonafide contractors /firms having experience / valid license for this type of field.

3. Estimated Cost : Rs. 99,675/-

4. Last date for submission of the tender : 03.01.2025 up to, 15.00 hrs.

5. Time allowed for completion of works : 10(ten) days after the issue of Work Order.

6. The intending tenderers may inspect the site on any working day during office time.

7. The intending tenderers will have to submit copy of valid Certificate of up to date Clearance of Trade License, Professional Tax, Income Tax, G.S.T and Credential along with tender papers for the work.

8. Sealed Tender addressed to The Commissioner of Police, 18, Lalbazar Street, Kolkata-700001 may be dropped in the box kept in front of the office of the Officer-in-Charge, Building Section, 2<sup>nd</sup> floor, Northern Building, 18, Lalbazar Street, Kolkata-700001 before the last date.

9. Sealed tender may also be sent by Registered Post / Speed Post superscribing the envelope as "Tender in response to Tender Notice No. T-282/Gen/24-25 dt. 26.12. 2024" so as to reach on or before the last date.

O.C. Buildings, Lalbazar, Kolkata.

Annexure- A
of knonen, bathroom, bedroom & diming room, Door replacment wuring the year 2024-25 [VIDE MEMO NO. 3381 De 21/10/2024]

|     |                   |   | 1  | Descriptio   | n of item  |  | 1            |        |               |                 |           | 10/2024 | 1  | ,                   |
|-----|-------------------|---|--|--|--|--|--------------|--------|---------------|-----------------|-----------|---------|--|---------------------|
|     |                   |   | Stripping off wor  | The second secon       | ACCES TO THE PARTY OF THE PARTY | walls, colings a                           | BRUATE HE    | Quant  |               | Rate            | Uni       | E       |  | Amount              |
|     |                   | age-45  | lead of 75m as di  | rected.  | second removing  | rubbish within                             | a            | 5.30   | aqmir         | 19:00           | achivi    |         | The state of the s | 480.70              |
|     |                   | tem-08  | mixing with water  | pats of bonding ages<br>having adheave a<br>rin proportion (1 bor<br>or's specification (0   | m macoi promii   | ng properties t                            | 99           | i.30   | agm tr        | 88.00           | »qm t     |         |  | 2226.40             |
|     |                   | age-189<br>6m-1   | including threating  | oor, calling etc.) with<br>amfering corners as<br>g. nosing and drip and | directed and re  | aking out joint                            | ×            |        |               |                 |           |         |  |                     |
|     |                   |   | is With 1:6 cement<br>(c) 15 mm thick pla  | mortar<br>sater  |  |  |              |        |               |                 |           |         |  |                     |
|     |                   | ge-196<br>m-10  | Acrylic Distemper<br>interior grade ac<br>including cleaning   | to interior wall, oci<br>rylic primer (as po<br>and smoothning of se   | ing with a coat of<br>ar manufacturer;<br>arface. Two Coats  | of solvent based<br>a specification)       | 25.3<br>147. |        | tmr.<br>Jentr | 151.00<br>70.00 | adust.    |         |  | 3820.30<br>10339.42 |
|     |                   | pr-53<br>n-15   | Supplying, fitting as<br>alcove, wardrobe et<br>mortar (1:2) includi<br>in -Charge in Groun                    | nd fixing Black Stone<br>Laid and jointed wit<br>ng grinding or polishi<br>ad Ploor  | slab used in Kitol<br>h necessary adhe,<br>ng as per direction   | nen alab,<br>sive Coment<br>n of Engineer- |              |        |               |                 |           |         |  |                     |
|     | 6 0-              |   | (a) Slab Thickness 2   | 0 to 25 mm   |  |  |              |        |               |                 | 1         |         |  |                     |
|     | 6 Page<br>Item    |   | height for external w  | n sheet glass panes ;<br>complete. (in all floor<br>ull)   | set in putty and fit<br>rs for internal wall   | ited and fixed<br>& upto 6 m               | 1.20         | sqr    | ntr           | 643.00          | squitt    |         |  | 771.60              |
|     | 7 Page            | -10   | i) 3 mm thick (weigh   | ing 7.4 kg/Sq.m)   |  |  | 1.20         |        |               |                 |           |         |  |                     |
|     | Item              | -02   | sed of 75 m  | s of plain cement con<br>at site and removing  | crete works, stack<br>rubbish as direct  | cing<br>ed within a                        | 1.20         | edst   | str           | 477,00          | admir     |         |  | 572.40              |
|     | 8 Page-           | 04 n  | al upto 150 mm. This<br>Ordinary Cement co-<br>ominal size) excludi-<br>oor as per rolevant I<br>Pakur Variety | acrete (mix 1:204) wit   | h graded stone ch<br>nforcement, if any,   | ips (20 mm<br>in ground                    | 0.20         | Cui    | W             | 939.00          | Culf      |         |  | 187.61              |
|     | 9 Page-<br>Item-  | 64 Si<br>35 m<br>su<br>in                                   | upplying, fitting & fi<br>atch with the existing<br>aidite at the back of<br>ixed with colouring               | cing lat quality Cerai<br>g work is 4 pos. of io<br>cach tile is finishing<br>oxide if poquired to m<br>of concrete surface, il<br>rials etc   | the joints with wh   | fixed with<br>tite cement                  | 0.20         | Cuk    | a 5           | 248.57          | Culid     |         |  | 1048.66             |
|     |                   | (A)   | Ploor  |  |  |  |              |        |               |                 |           |         |  |                     |
|     |                   | Limi  | ng white comout alu  | rtar (1:4) 20 mm thick<br>les uning cement @ 2<br>rry @ 0.20kg/Sq.m.   | c & 2 mm thick ce<br>.91 Kg/Sq.m & joi   | ment<br>int filling                        |              |        |               |                 |           |         | ,  |                     |
|     |                   | (m)   | Area of each tile upt  | 0.09 Sq.m  |  |  |              |        |               |                 |           |         |  |                     |
|     |                   | (i) (   | Coloured decorative  |  |  | 6  | .66          | sqmtr  | -             |                 |           |         |  |                     |
|     |                   | Witi  | h Sand Coment Most   | ar (1:4) 20 mm thick<br>as using coment & 2.   | & 2 mm thick cer<br>91 Kg/Sq-m & joir  |  |              | sqmu   | 75            | 5.00            | aquitr    |         | ,  | 5028.30             |
|     |                   | (a) A   | rea of each tile upto  |  |  |  |              |        |               |                 |           |         |  |                     |
| 10  | Page-15           | (i) C   | oloured decorative   |  |  | 26   | 20           |        |               |                 |           |         |  |                     |
|     | Item-30           | or re<br>inclu<br>for m                                     | ding mending good<br>ending damage will  | or and window frame<br>nt parts of the frame<br>all damacs complete.<br>be paid separately)  | including shutter<br>& refixing the san<br>(Concrete and bri   | for repair<br>ne<br>ck work                | .30          | 5Qm tr | 757           | 7.00            | sqmtr     |         |  | 19152.10            |
|     |                   |   | pto area 2.5 Sq.m  |  |  |  | . 1          |        |               |                 |           |         |  |                     |
| f   | age-152<br>tem-33 | Sasin   | g door and windows   |  |  | 6.0  |              | quitr  | 17.0          |                 | admtt.    |         |  | 581,91              |
| it  | em-01             | (iv) 25   | mm thick shutters  |  | 44 In an all   |  |              |        |               |                 |           |         |  | 102.00              |
| No  | on-               | Sishu,  | Gumar, Champ, Bac  | iam,Bhola, Mogra, H  | el of size 30 to 45<br>ellak.  | cm.(b) 1.8                                 | 9 84         | mir    | 2259          | 00              | edantr    |         |  | 4269.51             |
| Sec | hodule            | Two Oz<br>or equi<br>(33 mir<br>gnt que<br>mechar<br>chains | nily vs en) assemDed on n X 28 mm X 1.2 mm til nylon runners wit nism stainless stool j andP.VC. and bessen    | naster runners filer   | gon Hundred& Tw  | 4.32<br>renty                              | 2 49         | mtr    | 1122,         | 60 <sub>4</sub> | विद्युक्त |         |  | 4847,04             |
|     |                   | Conne   |  | The bottom end of<br>a height which are to<br>as per direction oft to  | be<br>ne   |  |              |        |               |                 |           |         |  |                     |

|  | - 3. Notices Associated Mark   |   | -      | 10.     |           |        | *************************************** |
|--|--|---|--------|---------|-----------|--------|---|
| and the second   | Description of item  | Quan                                    | tity   | Rate    | Unit      | Amount |   |
|  | sting & Fixing Factory made P.V.C. door frame of size 50   | 11.60                                   | Mtr    | 305.00  | Mtr       | A      | 3538.00                                 |
|  | with a wall thickness of 5 mm, made out of extrained 5 mm,   |   |        |         |           |        |   |
|  | niter cut at two corners and joined with two non of 1.5 mm.  |   | 140    |         |           |        |   |
|  | corackets of 15 mm x15 mm M.S. square tube. The two vertical door coffice are to be reinforced with 19 mmx 19 mm M.S. Square tube of 19  |   |        |         |           |        |   |
|  | gauge, weather seal to be provided through out the frame. The door   |   |        |         |           |        |   |
|  | frame shall be fixed with the wall using 65/100 mm long M.S. Screws  |   |        |         |           |        |   |
|  | through the frame by using P.V.C fasteners. A minimum of 4 Nos of  |   |        |         |           |        |   |
|  | acrews to be provided for each vertical member and minimum 2 Nos for<br>horizontal member etc. complete as per Manufacturer's specification and  |   |        |         |           |        |   |
|  | direction of Engineer-in-Charge.   |   |        |         |           |        |   |
| 15 Page-125  | Supplying, Pitting & Pixing 30 mm thick Factory made solid Panel PVC   | 3.00                                    | sqmtr  | 1943.00 | sigmtr    |        | 5829.00                                 |
| Item-15  | Door Shutter consisting of outer frame made out of M.S. tubes of 19  |   |        |         |           |        |   |
|  | gauge thickness and size 19 mmx19 mm for styles, top and bottom rails,<br>M.S. Irame shall have cost of steel primers of approved make and   |   |        |         |           |        |   |
|  | manufacture, M.S. frame covered with 5 mm th. heat moulded PVC "C"   |   |        |         |           |        |   |
|  | channel of size 30 mm th, 70 mm width out of which 50 mm shall be flat   |   |        |         |           |        |   |
|  | and 20 mm shall be tapered in 45 degree angle on either sides forming  |   |        |         |           |        |   |
|  | styles; and 5 mm th 95 mm wide PVC sheet out of which 75 mm shall be<br>flat and 20 mm tapered in 45 degree on the inner side to form top &  |   |        |         |           |        |   |
|  | bottom rail and 115 mm wide PVC sheet out of which 75mm shall be flat  |   |        | W 14    |           |        |   |
|  | and 20 mm shall be tapered on both sides to form lock rail. Top, bottom  |   |        |         |           |        |   |
|  | and lock rails shall be provided either side of the panel with 10 mm (5  |   |        |         |           |        |   |
|  | mmx2) th., 20 mm wide cross PVC sheet as gap insert for top rail and   |   |        |         |           |        |   |
|  | bottom rail. Paneling of 5 mm th. both side PVC sheet to be fitted in the M.S. frame welded/scaled to the styles farmis with 7 mm [5 mm <sup>2</sup> /2 mm]  |   |        |         |           |        |   |
|  | th.x15 mm wide PVC sheet beading on inner side and joined together   |   |        |         |           |        |   |
|  | with solvent cement adhesive. An additional 5 mm th. PVC strip of 20   |   |        |         |           |        |   |
|  | mm which is to be stuck on the interior side of the "C" channel using<br>PVC solvent adhesive etc. complete excluding all necessary hardwares as   |   |        |         |           | P      |   |
|  | PVC solvent adhesive etc. complete excluding all docessary handwares as  |   |        |         |           |        |   |
| 16 Page-140  | Supplying, fitting and fixing M.S. clamps for door and window frame  |   |        |         |           |        |   |
| Item-04  | made of flat bent ber, end bifurcated with necessary screws etc. by  |   |        |         |           |        |   |
|  | cement concrete(1:2:4) as per direction. (Cost of concrete will be paid  |   |        |         |           | ,      |   |
|  | separately)  | 2000                                    | 11.55  | 1       | 1,00.76   |        | 240.00                                  |
|  | (e) 40mm X 6mm, 125mm Length   | 12.00                                   | cach   | 20.00   | sach      |        | 240.00                                  |
| 17 Page-140  | from built hinges of approved quality fitted and fixed with steel acrews,  |   |        |         |           |        |   |
| item-05  | with 181   | £ 00                                    | 1      | 31.00   | éach      |        | 186.00                                  |
|  | (iv) 75mm. X 47mm. X 1,70mm.   | 6.00                                    | cach   | 43.00   | each      |        | 129.00                                  |
| 22-34 SWW  | (vi) 100mm. X 50mm. X 1.25mm   | 3.00                                    | cecn   | 43.00   | O-ACSI    |        | 125.00                                  |
| 18 Page-144  | Anodised aluminium barrel / tower / socker bolt [full covered] of  |   |        |         |           |        |   |
| Item-26  | approved manufactured from extruded section conforming to I.S. 204/74 fitted and fixed with cadmium plated acrews:   |   |        |         |           |        |   |
|  |  | 4.00                                    | each   | 88.00   | each      |        | 352.00                                  |
| 19 Page-141  | (v) 150mm iqng x 12mm dja. bolt<br>ij iron hasp bolt of approved quality fitted and fixed complete (oxidised)  | *************************************** |        |         |           |        |   |
| Item-10  | with   |   | -      |         |           |        |   |
|  | 16mm dia rod with centre bolt and round fitting.   |   |        |         |           |        |   |
|  | thy mean and the same  | 2.00                                    | each   | 159:00  | cach      |        | 318.00                                  |
| 20 Page-145  | (b) 250mm long  Anodised aluminium Aldrop / Sliding bolts of approved quality  | ,                                       |        | 200.00  |           |        |   |
| Item-28  | manufactured from extruded section conforming to I.S. specification (I.S.  |   |        |         |           |        |   |
|  | 2681/66) fitted and fixed complete.  |   |        |         |           |        |   |
|  |  | 4.00                                    | each   | 233.00  | week      |        | 932.00                                  |
|  | (i) 250mm x 16mm dia bolt.   | 4.00                                    | quen   | 200.00  | cacas     |        | 304100                                  |
| 21 Page-145<br>Item-30   | Anodised alignment D-type handle of approved quality manufactured from extruded section conforming to LS. specification (I.S. 230/72) fitted   |   |        |         |           |        |   |
| Titali Ou  | and fixed complete:  |   |        |         |           |        | 3                                       |
|  | a) With continuous plate base (Hexagonal/ Round rod)   |   |        |         |           |        |   |
|  | (vi) 150 mm grip x 10 mm dia rod.  | 6.00                                    | each   | 97.00   | each      |        | 582.00                                  |
| E 22 Page-107  | Supplying, fitting and fixing windows and captilators with or without  |   |        |         |           |        |   |
| Item-20  | integrated grills conforming to 18 1038-1975 and manufactured from   |   |        |         |           |        |   |
|  | rolled steel sections conforming to 15-7452-1974 with non-friction   |   |        |         |           |        |   |
|  | projecting type, box type hinges, glazing clips, lugs locking bracket,<br>handle place etc, including hoisting in position, straightening if required,   |   |        |         |           |        | ,                                       |
|  | fixing lugs in coment concrete (1:2:4) with stone chips 20 mm tlown  |   |        |         |           |        |   |
|  | cutting holes and mending good damages to match with existing suchace  |   |        |         |           |        |   |
|  | complete in all respect excluding glazing  |   |        |         |           |        |   |
|  | to 1 States over them an 32 (a) and 64 for   |   |        |         |           |        |   |
|  | (c) Extra over item no. 33 (a) and (b) for,  | 12.00                                   | cach   | 50.00   | cach      |        | 600:00                                  |
|  | (iv) Two point nose steel handle including fitting and fixing  | 12.00                                   | cach   | 35:00   | esch      |        | 429.00                                  |
| 23 Page-200  | (vi) steel peg stay 300 mm long including fitting and fixing a) Priming one coat on steel or other metal surface with synthetic oil  | 12.90                                   | egnitr | 29:00   | nomite    |        | 374.10                                  |
| item-1   | bound primer of approved quality including smoothening surfaces by   |   |        |         |           |        | Marianista                              |
| in the same of the | sand papering etc  |   | 4      |         |           |        |   |
| 24 Page-200  | (b) Priming one coat on timber or pleatered surface with synthetic oil   | 46.61                                   | sqmtr  | 38.00   | squitr    |        | 1770.99                                 |
| 24 Fage-200  | bound primer of approved quality including smoothening surfaces by   |   | eshasi | 20.00   | - quiu    |        | 1.570.00000                             |
|  | sand papering sto.   |   |        |         |           |        |   |
|  |  |   |        |         |           |        |   |
| 25 Page-200  |  |   |        |         |           |        |   |
| Item-2   | and brand including smoothening surface by sand papering etc.  |   |        |         |           |        |   |
|  | including using of approved putty etc. on the surface, if necessary :  |   |        |         |           |        |   |
|  |  |   |        |         |           |        |   |
|  | (a) On timber or plastered surface :   |   |        |         |           |        |   |
|  | With super gloss (hi-gloss) -  |   |        |         |           |        |   |
|  | No. of Section 1990 and 1990 a |   |        | 0.4     | 120000000 |        | 3775.01                                 |
|  | (iv) Two coats (with any shade except white)   | 46.61                                   | sqmtr  | 81.00   | adattr    |        | 3775.01                                 |
|  | (b) On steel or other metal surface :  |   |        |         |           |        |   |
|  | With super gloss [hi-gloss] -  |   |        |         |           |        |   |
|  | (iv) Two coats (with any shade except white)   | 12.90                                   | sqmtr  | 79.00   | squstr    |        | 1019.10                                 |

(1) (1) (1) (1) (1)

|                               | fitting and fixing stainless steel sink complete with waste   |       | -      | Rate         | Unit    | 1 1 | Amount                      |
|-------------------------------|---|-------|--------|--------------|---------|-----|-----------------------------|
|                               | and many stainless steel sink complete with month   |       |        |              |         |     | THE OWNER OF TAXABLE PARTY. |
| The state of the state of the | and two coats of painting of C.I. brackets  |       | 4      |              |         |     |                             |
|                               | Sink only   |       |        |              |         |     |                             |
| 1.00                          | (i) 530 mm X 430 mm x 180 mm  |       |        |              |         |     | •                           |
|                               | Supplying, fitting and fiving P Ut C  | . 1.  | 00 car | 3285.00      | each    |     | 200-                        |
| -02                           | approved make complete in position with necessary bolts, nuts etc.  | 8 of  |        |              | 100000  |     | 3285                        |
| -                             | a) With 'P' trap  |       |        |              |         |     | 70                          |
| 38 (2000 0)                   |   | 1.0   | 00 000 |              |         |     |                             |
| 28 Page-81<br>ltem-10         | Supplying, fitting and fixing Closet sest of approved make with lid sure  |       | CIIL   | h 1421.00    | each    |     | 1431.                       |
|                               | C.P. hinges, rubber buffer and brass screws complete.   | •     |        |              |         |     |                             |
|                               | (a) B.W.C   |       |        |              |         |     | 8                           |
|                               | ii) Plastic (bull-one)  |       |        |              |         |     |                             |
| 29 Page-36                    | ii) Plastic (hallow type) white   | 1.0   | 0 each |              |         |     |                             |
| Item-02                       | Supplying, fitting and fixing 10 litre P.V.C. low-down cistern conformir to 1.S. specification with P.V.C. fittings complete C.   |       |        | . 500.00     | each    |     | 380.0                       |
|                               | to I.S. specification with P.V.C. fittings complete, C.I. brackets including two costs of painting to bracket etc.  | 8 1.0 | O each | 1015.00      | cuch    |     | 1015.0                      |
| 30 Page-43                    |   |       | 27     |              |         |     |                             |
| Item-09                       | Supplying, fitting and fixing approved brand P.V.C CONNECTOR white flexible, with both ends coupling with beauty.   | 2.00  |        | 202700       |         |     |                             |
|                               | flexible, with both ends coupling with heavy brass C.P. nut. 15 mm dis  | 2.00  | 0 each | 147.00       | rach    |     | 294.0                       |
| 31 Page-03                    | Supplying, litting and fixing shower of approved brand and make   |       |        |              |         |     | , , , ,                     |
| Item-03                       | and make shower of approved brand and make  |       |        |              |         |     | 100                         |
|                               | (w)(iii) Chromium plated shower arm 240 mm long (Equivalent to Code<br>No. 536(A) & Model - Transcal / Sympton 1  |       |        |              |         |     |                             |
|                               | No. 536(A) & Mode! - Tropical / Surathing Special of ESSCO or similar brand).   | 1.00  | each   | 309.00       | emob    |     |                             |
|                               |   |       |        |              | anon'   |     | 309.00                      |
| 37 Page-06                    | (e) PTMT (Polytetra Bib Cook / Stop Cock ( Prayag or equivalent)  |       |        |              |         |     |                             |
| Item-07                       | 15 mm   | 6.00  | each   | 154,00       | each    |     |                             |
| 33 Page-82                    | Supplying, fitting and fixing best quality Indian make mirror 5.5 mm thick with silvering as rec (.5 t  |       |        |              | UMD11   |     | 924.00                      |
| Item-19                       | thick with silvering as per I.S.L. specifications supported on fibre glass frame of any colour, frame size 550 mm v. 4000 mm.   | 2:00  | each   | 613.00       | earth 1 |     |                             |
|                               | min value and min   |       |        |              |         |     | 1226.00                     |
| 34 Page-43                    | Supplying fitting and Gring and   |       |        |              |         |     |                             |
| Item-10                       | pipe, with PVC coupling at one end fixed with necessary clamps.   |       |        |              |         |     |                             |
|                               | (iii) 900 mm long   |       |        |              |         |     |                             |
| 35 Page-12                    | Supplying, fitting and fixing PVO-pipes of approved make of Schedule 80 (medium duty) conforming to ASTAD - PISS and the second of the second purple of the | 3.00  | each   | 75.00        | desch   |     | . The lab                   |
| Item-19                       | [medium duty] conforming to ASTAD 1785 and threaded to match with<br>GI Pipes as per [S: 1239 (Part ) and threaded to match with  |       |        |              |         |     | 150.00                      |
|                               | GI Pipes as per IS: 1289 (Part - I), with all necessary accessories,  |       |        |              |         |     |                             |
|                               | reducing socker, reducing to the country con nipple, longscrow,   |       |        |              |         |     |                             |
|                               | clamps, including outling pipes, making threads fitting, foring etc.  |       |        |              |         |     |                             |
|                               | complete in all respect including cost of all necessary littings as<br>required, jointing materials and in accessary littings as  |       |        |              |         |     | 2002                        |
|                               | required jointing materials and two coats of painting with approved paint<br>in any position above ground. Description  |       | 1      |              |         |     |                             |
|                               | measurements of total pine line total and be made on the centre line  | -     |        |              |         |     |                             |
|                               | payment will be made for accessories, specials. No acparate   | - 2   | 47     |              |         |     |                             |
|                               | be made separately:   |       |        |              |         |     |                             |
|                               |   |       |        |              |         |     |                             |
|                               |   |       |        |              |         |     |                             |
|                               | N Por Por   |       |        |              |         |     |                             |
|                               | a) For Exposed Work PVC Pipos   |       |        |              |         |     |                             |
| (1                            | Dial  |       |        |              |         |     |                             |
| 1                             | 5mm   |       |        |              |         |     | 1,1                         |
| 2                             | 5mm   | 6.00  | Mtr    | 101.00       | Mtr     |     |                             |
| 2.                            | ann.  | 3.00  |        |              | -AU     |     | 606.00                      |
|                               |   | 3.00  | Mtr    | 177.00       | Mir     |     | 531.00                      |
|                               |   |       |        |              |         |     |                             |
|                               | a with a special discussion of  |       |        | Add 9% for   | CGST    |     | 83634.15                    |
|                               |   |       |        | Add 9% for   |         |     | , 7527.07                   |
|                               |   |       |        | Total :      |         |     | 7527.07                     |
|                               |   |       |        | Add 1% for L |         |     | 98688.30                    |
|                               |   |       |        | The seas Die |         |     | 986.88                      |
|                               |   |       |        | Grand Tota   | de la   |     | 500.00                      |

RUPEES: NINETY-NINE THOUSAND SIX HUNDRED SEVENTY-PIVE ONLY.

Junior Engineer-III Kolkata Police Directorate Govt. of West Bengal

Assistant Engineer II Kolkata Police Directorate Goot, of West Bengal

## TERMS AND CONDITITON OF TENDERS

- 1. All works to be carried out in a manner according to specification for original work now in laid as the regional works in building department circle.
- 2. All materials, tools, plant and labour, the housing, water supply and transport will have to be provided by Contractor at their own cost inclusive of G.S.T. and other charges.
- 3. No extra work will be allowed without prior approval.
- 4. The contractors are requested to inspect the schedule of nature of works at site to save all eventualities connection with works any other information may be obtained from the OC, Buildings Office, Lalbazar. Any place of ignorance after submission of tender by the contractors will not be considered.
- 5. The quantities as shown against the item of work can be verified according to nature of works. Actual requirement to be done soon after containing the written approval of the Jt. CP(O), but contractors are liable for execution of varied quantities at their accepted rates. The rate of the addition item which are not found in the enclosed schedule will be based on building schedule of the regional works and buildings circle subject to approval of proper authority.
- 6. The contractors should submit tender enclosed with Trade License, Income Tax return, GST, Credential, Under taking of black listed failure to which will be disqualified.
- 7. The work will be taken up within 07(Seven) days after receipt of work order, failing to which legal action may be taken against the firm.
- 8. The Commissioner of Police Kolkata reserves the right to reject any/or all the tender rates without assigning any reason and also to distribute the said works among the tenders. There is no guarantee that the lowest tender will be accepted by the authority concern.
- Tender addressed to the Commissioner of Police, Kolkata should be sent in a sealed cover super scribed name of tender to be dropped in the sealed TENDER BOX to be kept the OC, Buildings Office, LaLbazar at 18, Lalbazar Street, Kolkata-700 001 within 15.00 hrs on last date.
- 10. The Tender Committee will open the sealed tender in the Committee Room of Lalbazar, The Agencies may be present or send their authorized representative at the time of opening the sealed tender box.

O.C., Buildings, Lalbazar.

# PERCENTAGE RATE TENDER AND CONTRACT FOR WORKS: GENERAL RULES AND DIRECTIONS FOR THE GUIDANCE OF CONTRACTS.

 All works proposed for execution by contract will be notified in a form of invitation of tender posted in public places and signed by the OC, Buildings Office, Lalbazar.

This form will state the work to be carried out, as well as the date of submitting and opening of tenders and the time allowed for carrying out the work, design and drawings and any other documents required in connection with work signed for the purpose of identification by the OC, Buildings Office, Lalbazar shall also be open for inspection by the contractor at the office of the OC, Building, Lalbazar during office hours.

- 2. In the event of the quotation being submitted by a firm, it must be signed separately by each member thereof or in the event of the absence of any partner it must be signed on his behalf by a person holding a power of attorney authorizing him to do so. Such power of attorney is to be produced with the tender and same in the case of a firm carried on by one member of a joint family, it must be disclose that the firm is duly registered under the Indian partnership Act.
- 3. Receipts for payment made on account of work, when executed by a firm, must also be signed by the several partners except where the contractors are described in their tender as a firm in which case the receipts must be signed in the name of the firm by one of the partners or by some other person having authority to give effectual receipts for the firm.
- 4. Any person who submits a tender shall fill up the usual printed form, stating at what rate he is willing to undertake each item of the work. Tenders which propose any alteration, in the work specified in the said form of invitation of tenders or in the time allowed for carrying out the work, or which contain any other conditions of any sort, will be liable to rejection. No single tender shall include more than one work but contractors who wish to quote for two or more works shall submit a separate tender for each. Tenders shall have the name and number of the work to which they refer written outside the envelope.
- 5 The Committee will open tenders in the presence of any intending contractors who may present at the time and will enter the amounts of the several tenders in a comparative statement in a suitable form.
- The accepting authority reserves the right to reject any or all the tender without assigning any reasons and he will not be bound to accept either the lowest tender or any of the tenders.

O.C., Buildings, Lalbazar.