Government of West Bengal Office of the Commissioner of Police 18, Lalbazar Street, Kolkata-700 001.

No. T-308/Gen/24-25

Date - 07.01.2025

NOTICE INVITING TENDER

Sealed tenders in printed form are invited for the following works from eligible tenderers as per particulars given below:

Name of work Essential thorough repairing and renovation of OC's Rest Room and 1. 03 Nos. toilet & sewerage line at Cossipore PS at 58/1, B. T. Road, Kolkata. (Details in ANNEXURE-A) 2, Eligibility All bonafide contractors /firms having experience / valid license for this type of field. Estimated Cost 3. Rs. 72,197/-Last date for submission of the tender 4. 15.01.2025 up to, 15.00 hrs. Time allowed for completion of works : 10(ten) days after the issue of Work Order. 5.

6. The intending tenderers may inspect the site on any working day during office time.

7. The intending tenderers will have to submit copy of valid Certificate of up to date Clearance of Trade License, Professional Tax, Income Tax, G.S.T and Credential along with tender papers for the work.

Sealed Tender addressed to The Commissioner of Police, 18, Lalbazar Street, Kolkata-700001 may be dropped in the box kept in front of the office of the Officer-in-Charge, Building Section, 2nd floor, Northern Building, 18, Lalbazar Street, Kolkata-700001 before the last date.

9. Sealed tender may also be sent by Registered Post / Speed Post superscribing the envelope as "Tender in response to Tender Notice No. T-308/Gen/24-25 dt. 07.01. 2025" so as to reach on or before the last date.

> O.C. Buildings, Lalbazar, Kolkata.

Annexure- A.

as of work: Estimate for thorough Repairing & Renovation of Officer-in-charge's Rest room & Three(03) No. Of Toiletes & Its Scwerage three At Cossipore PS Kolkata (During the year 2024-25). [WIDE MEMO: 3910 Dt: 19/11/2024]

Puge & Item No	Description of item	Quan	tity	Rate	Unit	Amount	
rage-11 item-10	Stripping off wors out plaster and raking out joints of walls, cellings etc. upto any height and in any floor including removing rubbish within a lead of 75m as directed.	40.20 sqmtr		19.00	squatr	763.80	
Page-45 item-98	of ron as directed. Applying 2 coats of bonding agent with synthetic multi functional rubber emulsion having adhesive and water proofing properties by mixing with water in proportion [1 bonding agent : 4 water : 6 cement] as per Mamufacturer's specification [Cement to be supplied by the Department]	40.20	adus tr	88.00	squatr	3537.6	
Page-45 ftem-05	*	7.26	aqmtr	90:00	edmp	648.0	
ttern-vs	Cleaning the concrete surface by removing dirt and debris, marking defective locations and removing loose concrete by careful stripping untill hard surface is exposed, cutting the concrete to regular shape, wire brushing the exposed surface and removing debris from site complete as per direction of the Engineer - in - Charge	•	* :				
Page-189 Item-1	Plaster (to wall, floor, ceiling etc.) with saint and coment mortar including round off or chamfering corners as directed stad taking out joints including thronting, nosing and drip course, scatholdes/staging where necessary (Ground floor).[Excluding cost of chipping over concrete surface]	ga. 1949		,			
	(i) With 1:6 cement mortar						
	(c) 15 mm thick plaster	40.20	sqmb	151:00	squitr	6070.1	
Page-204 Item-05	ib Residering the surface of walls and ceiting with white cement based wall putty of approved make and brandfit. Some thick!	19.92	equatr	110.00	squatr	2191.5	
Page-196 Item-10	Acrytic Distemper to interior wall, ceiling with a coat of solvent based interior grade acrytic primer (as per manufacturer's specification) including cleaning and smoothning of surface. Two Coats	27.12	squitr	76:00	squitr	- 1898.	
Page-205 ltem-01	Supplying best indian sheet glass panes set in purity and fitted and faced with nalls and purty complete. (In all floors for internal wall accepts to in height for external wall)						
Page-11 Item-06	(i) 3 mm thick (weighing 7.4 kg/Sq.m) Diamantling artificial stone flooring upto 50 nam, thick by carefully, chiseffing without damaging the base and removing rubbish as directed within a lead of 75 m	7.20	edurn. edung.	\$0,00	squatr sqmtr	, 365. 360.	
Page-24 Item-04	Ordinary Cement concrete (mix 1:2:4) with graded attain chips (20 mm nominal size) excluding abuttleting and feliabecement, if any, in ground floor as per relevant is codes.						
	n) Pakur Variety	0.36	CuM	5248.57	CuM	1889	
Page-64 Item-35	Supplying, fitting & fixing 1st quality Ceramic tiles in walls and floors to match with the existing work & 4 nos. of key stones [10mm] used with analytic at the back of each tile & finishing the joints with while cement mixed with colouring oxide if required to match the colour of tiles including roughering of concrete surface, if necessary he by synthetic adhesive & grout materials etc			L			
	(A) Floor						
	With Sand Cement Mortar (1:4) 20 mm thick & 2 mm thick cement slarry at back side of tiles using cement @ 2.91 kg/Sq.m & joint filling using white cement slarry @ 0.20kg/Sq.m.						
	(a) Area of each tile upto 0.09 Sq.m						
	(i) Coloured decorative	7.20	sqmtr	755:00	sqmtr	5436	
	(B) wall						
	With Sand Cement Moriar (1.4) 20 mm thick & 2 mm thick coment slurry at back side of tiles using coment & 2.91 Kg/Sq.m & joint filling using white cement slurry @ 0.20kg/Sq.m.						
	(a) Area of each tile upto 0.09 Sq.m			100000000000000000000000000000000000000			
	(i) Coloured decorative	20.28	sqmtr	757:00	squitr	15351.	
Page-200 Item-1	a) Priming one coat on steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc.	18:64	sqmtr	29,00	sdm _{ft} .	540.	
Page-200 Item-1	(b) Priming one coat on timber or plastered surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand	2,52	agmtr	38:00	aquotr	95	

1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	A Parantag with heat quality synthetic enamed paint of superior and brand including sunnothering surface by superior sup	de libraria					
0	Visit super gloss (hirgious)	ar gerila	2				
0	Visit super gloss (hirgious)	un gertla-					
0							
ţ.	ivi Two coats (with any shade except white)	2 107	somtr	81.00	soutr		204.1
,		2.02	-pubmit.				775-7855
	b) On steel or other metal surface :				4.4		
	With super gloss (hi-gloss) -	No. etc.	scimbr	79.00	squitr ,		1472.50
	ie) Two coats (with any shade except white)	110,04	activer	25.00	edino /		111111
item-30	abour for taking out door and whistly hame sociating shares for or replacement of different parts of the frame & selbting the same including mending good all damage complete. [Concrete and Isrick for mending damage will be paid separately]						
	(a) Upto area 2.5 Sq.m	4.80	sqmu	119.00	admir		571.2
	Supplying, Fitting & Fixing Factory made P.V.C. door frame of size	50 14.40	Mtr	305.00	Mtr		4392.0
Item-04 1	mmx47 mm with a wall thickness of 5 mm, made out of extraded PVC sheet miter cut at two corners and joined with two nos of 1.5 mm x15 mm M.S. square tube. The two vertice profiles are to be reinforced with 19 mmx 19 mm M.S. Square tub gauge, weather sent to be provided through out the frame. The dot shall be fixed with the wall using 63/100 mm long M.S. Sorews in the frame by using P.V.C fasteness. A minimum of *Nee of screw provided for each vertical nember and himmum 2 Nes for horizon	5 mm, mm al door se of 19 or frame wough s to be					
	member etc. complete as per Manufacturer's specification and dir	rection of					
	Engineer-in-Charge.	1		`			,
			,				
				12000040000		*	
Item-15	Supplying, Fitting & Pixing 30 mm thick Pactory made solid Func- Door Shutter committing of outer frame stade out of M.S. takes of	19	adult	1943.00	edungs		8743.5
	gauge thickness and size 19 mm. If mis for a view to an about Mr. S. frame shall have out of scaled primary of upproved made and Mr. S. frame thall have count of which your of, frost moulded of channel of size 30 mm th. To mis with our of which 50 and shall and 20 mm shall be tripered in 46 degree single on other sides for styles; and 5 mis th. 95 mm wide PVC wheet out of which 75 mm that and 20 mm tapered in 45 degree on the inner side to form top bottom rail and 115 mm wide PVC sheet out of which 75 mm abad and 20 mm shall be tapered on both sides to form-look and Top, and lock rails shall be provided either side of be panel whit to missel the 10 mm wide or one PVC sheet as gap insert for top wall	IC 107 It be that ming tainall be 3 65 It be day hothern for (5					
	bottom rail. Paneling of 5 mm th. both sade PVC alrest to be sitted	in the				1	
	M.S. frame welded/scaled to the styles oralls with 7 mm (5 mm)	2 mm)					
	th.x15 mm wide PVC sheet beating on inner side and joined tage solvent cement adhesive. An additional 5 mm th. PVC strip of 20	man with					
	which is to be stuck on the interior side of the "C" charmel using	PVC		-			
	solvent adhesive etc. complete excluding all mecessary hardwares	as per					
	direction of Engineer-in-Charge. In-ground floor	2					
		. 1				,	
17 Page-140 Item-04	Supplying, fitting and fixing M.S. clamps for door and window for of flat bent bar, end bifurcated with necessary screws etc. by ear concreto(1:2:4) as per direction. (Cost of concrete will be paid sep	tasa					
ruem-04		74					
tten-04		- 1	_	nin ma	-		240
	(c) 40mm X 6mm, 125mm Length	12.0	00 each	20.00	each		240.0
18 Page-140 item-05	(c) 40mm X 6mm, 125mm Length Iron butt hinges of approved quality fitted and fixed with steel so with ISI		00 each	20.00	each		240.

84	Description of item		Quantity		Unit	Amount	
No	Anodised aluminium Akirop / Siking boils of approved quality			Total State of the last of			
5	Anodised aluminum Autrop / Stating conforming to I.S. specification (I.S. manufactured from extruded section conforming to I.S. specification (I.S.						
	2681/66) fitted and fixed complete.						
	2001/00/ 41111			233.00	each		1398.00
	(i) 250mm x 16mm dia bolt.	6.00	each	255.00	CHL.		
5	Anodised aliminium D-type handle of approved quality manufactured from						
	Anonised administration of the last specification (I.S. 230/72) fired and	. 3					
	fixed complete:						
	a) With continuous plate base (Rexagonal/ Round rod)	6.00	each	97.00	each	-	582.00
	(vQ 150 mm grip x 10 mm dia rod.	0.00				,	
3	Making one set of scaffolding only for replacing glass panels, painting, uprooting plant and another repairing works of building and 384P works						
3	for many and modes only with 10 cm, dis barreboo as main posts at the rate						
	of I make penting to centre and 7.5 cm. dia bamboo fics (6 U. 73 ment						
	Bring and Svine with necessary coir, Bails etc. as per Greenon of						
	the Engineer-in charge. (This item should be executed only after prior			* 5			
	approval of the Engineer-in charge). Firstly, one number to be paid and then labour rate for shifting up to further nineteenth (19) times @ 10%						-
	time to be considered if necessary further after twenty times of total	-					
	use, another one number new and labour rate for shifting to be considered	+ 1					
	accordingly.						
		1.00	- 250	894:00	each		524.00
	a) 5.2 metre height	1.09	ERCE	July 1. Out			
P		1			1		2.4
18	Supply of UPVC pipes (B Type) & finings conforming to 18-18592-1992						
23	Supply of our to below to 1974	797					-
	(A) (i) Single Socketed 3 Meter-Length						
	(A) (I) Single Societies 5 meter-sconges		· Cres	292,00	Mitt		1752:0
	(b) 110 mm	6.00	Mtr	298.00	140		
	an number of a Mater Langth	30					
	(ii) Double Socketed 3 Meter Longth			315/00	Mur		945.0
	(b) 110 mm · .	3.00	Mtr	313.00	pa b		
	1 Dentil Gerberg 1 2 Mater Length	1					
	(v) Double Socketed 1.2 Meter Length	War I		222.00	Mtr		386.4
	(b) 110 mm	1,20	Mu	322.00	MILL		
		1					
*		ã		1000			60578.0
		. ?		Add 9	% for DGST		8452.0
		1		Add 9	% for SGST	-	5452.0
		- :		- 6	rétal=		71482.
		1		Add 196	for L.W.Com		714.8
		1		(Select	nd Tutal -	AC-10-	72196.8
				-	E 0-1/-		
		. 0			1	-	197.00

RUPERS: SEVENTY-TWO THOUSAND ONE HUNDRED WINETY-SEVEN ONLY.

comme

JE-III KPD
Junior Engineer-III
Wolkata Police Directorate
Govt. of West Bengal

Technically Checked & Verified

Assistant Regimeer-II Kolkata Poice Directorate Govt. of West Report

TERMS AND CONDITITON OF TENDERS

- 1. All works to be carried out in a manner according to specification for original work now in laid as the regional works in building department circle.
- 2. All materials, tools, plant and labour, the housing, water supply and transport will have to be provided by Contractor at their own cost inclusive of G.S.T. and other charges.
- 3. No extra work will be allowed without prior approval.
- 4. The contractors are requested to inspect the schedule of nature of works at site to save all eventualities connection with works any other information may be obtained from the OC, Buildings Office, Lalbazar. Any place of ignorance after submission of tender by the contractors will not be considered.
- 5. The quantities as shown against the item of work can be verified according to nature of works. Actual requirement to be done soon after containing the written approval of the Jt. CP(O), but contractors are liable for execution of varied quantities at their accepted rates. The rate of the addition item which are not found in the enclosed schedule will be based on building schedule of the regional works and buildings circle subject to approval of proper authority.
- 6. The contractors should submit tender enclosed with Trade License, Income Tax return, GST, Credential, Under taking of black listed failure to which will be disqualified.
- 7. The work will be taken up within 07(Seven) days after receipt of work order, failing to which legal action may be taken against the firm.
- 8. The Commissioner of Police Kolkata reserves the right to reject any/or all the tender rates without assigning any reason and also to distribute the said works among the tenders. There is no guarantee that the lowest tender will be accepted by the authority concern.
- Tender addressed to the Commissioner of Police, Kolkata should be sent in a sealed cover super scribed name of tender to be dropped in the sealed TENDER BOX to be kept the OC, Buildings Office, LaLbazar at 18, Lalbazar Street, Kolkata-700 001 within 15.00 hrs on last date.
- 10. The Tender Committee will open the sealed tender in the Committee Room of Lalbazar, The Agencies may be present or send their authorized representative at the time of opening the sealed tender box.

O.C., Buildings, Lalbazar.

PERCENTAGE RATE TENDER AND CONTRACT FOR WORKS: GENERAL RULES AND DIRECTIONS FOR THE GUIDANCE OF CONTRACTS.

 All works proposed for execution by contract will be notified in a form of invitation of tender posted in public places and signed by the OC, Buildings Office, Lalbazar.

This form will state the work to be carried out, as well as the date of submitting and opening of tenders and the time allowed for carrying out the work, design and drawings and any other documents required in connection with work signed for the purpose of identification by the OC, Buildings Office, Lalbazar shall also be open for inspection by the contractor at the office of the OC, Building, Lalbazar during office hours.

- 2. In the event of the quotation being submitted by a firm, it must be signed separately by each member thereof or in the event of the absence of any partner it must be signed on his behalf by a person holding a power of attorney authorizing him to do so. Such power of attorney is to be produced with the tender and same in the case of a firm carried on by one member of a joint family, it must be disclose that the firm is duly registered under the Indian partnership Act.
- 3. Receipts for payment made on account of work, when executed by a firm, must also be signed by the several partners except where the contractors are described in their tender as a firm in which case the receipts must be signed in the name of the firm by one of the partners or by some other person having authority to give effectual receipts for the firm.
- 4. Any person who submits a tender shall fill up the usual printed form, stating at what rate he is willing to undertake each item of the work. Tenders which propose any alteration, in the work specified in the said form of invitation of tenders or in the time allowed for carrying out the work, or which contain any other conditions of any sort, will be liable to rejection. No single tender shall include more than one work but contractors who wish to quote for two or more works shall submit a separate tender for each. Tenders shall have the name and number of the work to which they refer written outside the envelope.
- 5 The Committee will open tenders in the presence of any intending contractors who may present at the time and will enter the amounts of the several tenders in a comparative statement in a suitable form.
- The accepting authority reserves the right to reject any or all the tender without assigning any reasons and he will not be bound to accept either the lowest tender or any of the tenders.

O.C., Buildings, Lalbazar.