Government of West Bengal Office of the Commissioner of Police 18, Lalbazar Street, Kolkata-700 001.

No. T-015/PHE/25-26

Date - 08.05.2025

NOTICE INVITING TENDER

Sealed tenders in printed form are invited for the following work from eligible tenderers as per particulars given below:

1. Name of work

: Repairing of ceiling & wall of kitchen, bathroom, bedroom & dining room, window glasses & inside painting of Quarter No. 11, Block-K, 2nd floor of H.C. Block PHE at Sec-III, Salt Lake, Kolkata. (Details Estimate annexed)

2. Eligibility

All bonafide contractors /firms having experience for essential

civil/elec. work.

3. Estimated Cost

: Rs. 82,748/-

Last date for submission of the tender

19. 05. 2025 up to 15.00 hrs.

5. Time allowed for completion of work

10(ten) days after the issue of Work Order

6. The intending tenderers may inspect the site on any working day during office time.

7. The intending tenderers will have to submit copy of valid Certificate of up to date Clearance of Trade License, Professional tax, Income Tax, G.S.T and Credential along with tender papers for the work.

8. Sealed Tender addressed to The Commissioner of Police, 18, Lalbazar Street, Kolkata-700001 may be dropped in the box kept in front of the office of the Officer-in-Charge, Building Section, 2nd floor, Northern Building, 18, Lalbazar Street, Kolkata-700001 before the last date.

 Sealed tender may also be sent by Registered Post / Speed Post super scribing the envelope as "Tender in response to Tender Notice No. T-015/PHE/25-26 dt. 08.05.2025" so as to reach on or before the last date.

> O.C. Buildings(PHE) Lalbazar, Kolkata.

Name of work: Estimate for Repairing of cilling & wall of kitchen, bathroom, bedroom & dinning room, window glasses & inside painting .OF H.C.BLOCK SEC-III, Salt lake ,QUATER NO.11 2 ND FL BLOCK NO-K (During the year 2025-2026). [IBMS Req. No. 3341 Dt: 02/03/2025]

S1 No	Page &	Stripping off worn out plaster and raking out joints of walls, celings etc. upto any height and in any floor including removing rubbish within a lead of 75m as directed.	Quantity		Rate	Unit	Amount	
1	Page-I1 Item-10		5.00	sqmtr	19.00	sqmtr	95.00	
	Page-40 Item-27	Cement concrete (1:1.5:3) with graded stone chips 5.6 mm size with hexagonal square mesh wire netting, I.R.C. fabric mesh or X.P. M. fitted and fixed after tying the existing reinforcement on concrete without						
		distributing the same and with proper scarping and cleaning the reinforcement and disturbed concrete with wire brush etc. after applying a coat of cement including the cost of wire netting I.R.C or X. P. M. & cost of all handling and scaffolding complete as per direction of						
		Engineer-in -charge.						
3	Page-45	b) 25 mm thick a) Applying 2 coats of bonding agent with synthetic	5.00	sqmtr	522.00 88.00	sqmtr sqmtr	2610.00 880.00	
	ltem-08	water proofing properties by mixing with water in proportion (1 bonding agent : 4 water : 6 cement) as per Manufacturer's specification [Cement to be supplied by the Department]	10.00	aqmu	35.50	aqiitu	300.00	
	Page-45		5.00	sqmtr	90.00	sqmtr	450.00	
	Item-05	Cleaning the concrete surface by removing dirt and debris, marking defective locations and removing loose concrete by careful stripping untill hard surface is exposed, cutting the concrete to regular shape, wire		•		in.		
		brushing the exposed surface and removing debris from site complete as per direction of the Engineer - in -						
	D 100	Charge	•				44 - 1 - 1-1	
	Page-189 ltem-1	Plaster (to wall, floor, ceiling etc.) with sand and cement mortar including round off or chamfering corners as directed and raking out joints including throating, nosing and drip course, scaffolding/staging where necessary (Ground floor). [Excluding cost of chipping over concrete surface]						
		(i) With 1:6 cement mortar						
		(c) 15 mm thick plaster (ii) With 1:4 cement mortar	5.00	sqmtr	151.00	sqmtr	755.00	
	ltem-05	(c) 10 mm thick plaster (b) Rendering the surface of walls and ceiling with white cement based wall putty of approved make and brand(1.5mm thick)	5.00 10.00	sqmtr sqmtr	133.00 110.00	sqmtr sqmtr	665.00 1100.00	
	Page-196 ltem-10	Acrylic Distemper to interior wall, ceiling with a coat of solvent based interior grade acrylic primer (as per manufacturer's specification) including cleaning and	136.00	sqmtr	70.00	sqmtr	9520.00	
		smoothning of surface. Two Coats						
	Item-15	Supplying, fitting and fixing Black Stone slab used in Kitchen alab, alcove, wardrobe etc. laid and jointed with necessary adhesive Cement mortar (1:2) including grinding or polishing as per direction of Engineer-in -Charge in Ground Floor						
		(a) Slab Thickness 20 to 25 mm	1.00	sqmtr	643.00	sqmtr	643.0	
	item-01	Supplying best Indian sheet glass panes set in putty and fitted and fixed with nails and putty complete. (In all floors for internal wall & upto 6 m height for external wall)						
		(i) 3 mm thick (weighing 7.4 kg/Sq.m)	2.00	sqmtr	477,00	sqmtr	954.00	
	tem-2	Dismantling all types of plain cement concrete works, stacking serviceable materials at site and removing rubbish as directed within a lead of 75 m.in ground floor including roof (a) upto 150 mm. thick						
			0.20	sqmtr	939.00	sqmtr	187.80	
	tem-4	Ordinary Cement concrete (mix 1:2:4) with graded stone chips (20 mm nominal size excluding shuttering and reinforcement, if any, in ground floor as per relevant IS codes. a) Pakur Variety						
	age-64	Supplying, fitting & fixing 1st quality Ceramic tiles in	0.20	Cu.M.	5248.57	Cu.M.	1049.7	
1	tem-35	walls and floors to match with the existing work & 4 nos. of key stones (10mm) fixed with araldite at the back of each tile & finishing the joints with white cement mixed with colouring oxide if required to match the colour of tiles including roughening of concrete surface, if necessary or by synthetic adhesive & grout						
		materials etc.						
		A) Floor With Sand Cement Mortar (1:4) 20 mm thick & 2 mm thick cement alurry at back side of tiles using cement @ 2.91 Kg/Sq.m & joint filling using white cement alurry @ 1.20kg/Sq.m. Jacks of each tile pure 0.09 Sq.m.						
		a) Area of each tile upto 0.09 Sq.m i) Coloured decorative		200,000				
			4.50	sqmtr	755.00	sqmtr	. 3397.50	

S1 No	Page &	Description of item	Quanti	ity	Rate	Unit	Amount
		(B)Wall With Sand Cement Mortar (1:3) 15 mm thick & 2 mm thick cement slurry at back side of tiles using cement @ 2.91 Kg/Sq.m & joint filling using white cement slurry @ 0.20kg/Sq.m					
	Page-152 Item-30	(a) Area of each tile upto 0.09 Sq.m (i) Coloured decorative Labour for taking out door and window frame including abutter for repair or replacement of different parts of the frame & refixing the same including mending good all damages complete. (Concrete and	20.00	sqmtr	757.00	sqmtr	15140.00
		brick work for mending damage will be paid separately) (a) Upto area 2.5 Sq.m	3.00	sqmtr	119.00	aqmtr	357.00
	Page-125 Item-15	Supplying, Fitting & Fixing 30 mm thick Factory made solid Panel PVC Door Shutter consisting of outer frame made out of M.S. tubes of 19 gauge thickness and size 19 mmx19 mm for styles, top and bottom rails, M.S. frame shall have cost of steel primers of approved make and manufacture, M.S. frame covered with 5 mm th. heat moulded PVC "C" channel of size 30 mm th, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on either sides forming styles; and 5 mm th. 95 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm tapered in 45 degree on the inner side to form top & bottom rail and 115 mm wide PVC sheet out of which 75mm shall be talt and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided either side of the panel with 10 mm (5 mmx2) th., 20 mm wide cross PVC sheet as zep ninest for top rail and bottom rail. Paneling of 5 mm th.					
		both side PVC sheet to be fitted in the M.S. frame welded/scaled to the styles &rails with 7 mm (5 mm ² mm) th.x15 mm wide PVC sheet beading on inner side and joined together with solvent cement adhesive. An additional 5 mm th. PVC strip of 20 mm which is to be stuck on the interior side of the "C" channel using PVC solvent adhesive tc. complete excluding all necessary hardwares as per					
15	Page-140	direction of Engineer-in-Charge. In ground floor. Iron butt hinges of approved quality fitted and fixed with steel	3.20	sqmtr	1943.00	aqmtr	6217.60
	ltem-5	screws, with ISI mark. (iv) 75mm. X 47mm. X 1.70mm.	8.00	each	31.00	each	· 248.00
16	Page-141 ltem-10	 i) Iron hasp bolt of approved quality fitted and fixed complete (oxidised) with 16mm dia rod with centre bolt and round fitting. (b) 250mm long. 	4.00	each	159.00	each	636.00
17	Page-145 Item-28	Anodised aluminium Aldrop / Sliding bolts of approved quality manufactured from extruded section conforming to I.S. specification (I.S. 2681/66) fitted and fixed complete.					
		(i) 250mm x 16mm dia bolt	4.00	each	233.00	each	932.0
18	Page-145 ltem-30	Anodised aliminium D-type handle of approved quality manufactured from extruded section conforming to I.S. specification (I.S. 230/72) fitted and fixed complete:					
		(a) With continuous plate base (Hexagonal / Round rod)					
19	Page-104 Item-13	(vii) 150 mm grip x 12 mm dia rod. (a) M.S.or W.I. Ornamental grill of approved design joints continuously welded with M.S, W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor.	4.00	each	111.00	each	444.0
		(Add extra @ 1% for each addl. floor upto 4th floor and @ 1.25% for each addl. floor above 4th floor)					
20	Page-245 Item-15	(i) Grill weighing above 10 Kg./sq.mtr and up to 16 Kg./sq.mtr. Supplying, fitting & fixing of 2-Track / 3-Track Aluminium sliding Window of all Aluminium sections viz. window frame (top, bottom & side frame), shutter (top, bottom, side & interlock member) made of aluminium alloy extrusions conforming to IS 733-1983 & IS 1285-1975, annodised conforming to IS 1868-	0.25	gnti.	9888.00	qntl	2472.0
		1983, fitted with all other accessories viz. PVC roller, EPDM gasket, maruti lock, screws etc. including labour charges			ie di		
		for fitting & fixing of aluminium 2-track/3-track sliding window with fixing of glass (excluding cost of glass) all complete as per architectural drawings and direction of Engineer-in-charge. 10-12 Micron thickness Annodizing					
		film Natural white			10		
2	Page-16	125 mm. thick brick work with 1st class bricks in cement mortar (1:4)	14.00	Kg.	448.00	Kg.	6272.0
	ltem-16	in ground floor.	2.00	sqmtr sqmtr	736.00 29.00	sqmtr sqmtr	1472 464
	Page-200	bound primer of approved quality including smoothening surfaces by sand papering etc		sqmtr	38.00	sqmtr	1052
2	Item-1	bound primer of approved quality including smoothening surfaces by sand papering etc.					
2	Page-200 Item-2	(A) Painting with best quanty synthetic charact paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary:					
		(a) On timber or plastered surface :					
		With super gloss (hi-gloss) -	27.70	sqmtr	81.00	sqmtr	2243
		(iv) Two coats (with any shade except white) (b) On steel or other metal surface :	21.10	aqını	-		

Page 2 of 3

	age &	Description of item	Quan	tity	Rate	Unit	Amount	
		S & P						
25 Pag	ge-03 m-03	Supplying, fitting and fixing shower of approved brand and make	100			*		
		(a)(iii) Chromium plated shower arm 240 mm long (Equivalent to Code No. 536(A) & Model - Tropical / Sumthing Special of ESSCO or similar	1.00	each	309.00	each		309.00
		hyandi (h) Polythene overhead shower of approved make 15 mm X 125 mm	1.00	each	154.00	each		154.00
26 Pa	ge-82 m-19	Supplying, fitting and fixing best quality Indian make mirror 5.5 mm thick with silvering as per I.S.I. specifications supported on fibre glass frame of any colour, frame size 550 mm X 400 mm	1.00	each	613.00	each		613.00
27 Pa	ge-82 m-22	Supplying, fitting and fixing towel rail with two brackets. (iii) 25 mm dia. and 750 mm long	1.00	each	475.00	each		475.00
28 Pa Ite	ge-42 m-06	Supplying, fitting and fixing stainless steel sink complete with waste fittings and two coats of painting of C.I. brackets. (a) Sink only (i) 530 mm X 430 mm x 180 mm	1.00	each	3285.00	each		3285.00
0 D	47							
29 Pa Ite	m-09	Supplying fitting and fixing approved brand P.V.C. CONNECTOR white flexible, with both ends coupling						
		with heavy brass C.P. nut, 15 mm dia.	2.00	each	147.00	each		294.00
30 Pa	ge-43 m-10	(v) 900 mm long Supplying fitting and fixing approved brand 32 mm	2.00	cacn	147.00	cacii		251100
		dia.P.V.C. waste pipe, with PVC coupling at one end fitted with necessary clamps.						
		(iii) 900 mm long	2.00	each	75.00	each		150.00
31 Pa	ge-06 m-07	Supplying, fitting and fixing bib cock or stop cock.	2.00					
		(e) PTMT (Polytetra Bib Cock / Stop Cock (Prayag or equivalent) 15 mm	4.00	each	154.00	each		616.00
32 Pa	ge-12 m-19	Supplying, fitting and fixing PVC pipes of approved make of Schedule 80 (medium duty) conforming to ASTMD - 1785 and threaded to match with GI Pipes as per IS: 1239 (Part - I). with all necessary accessories, specials viz. socket, bend, tee, union, cross, elbo, nipple, longscrew, reducing socket, reducing tee, short piece etc. fitted with holder bats clamps, including cutting pipes, making threads, fitting, fixing etc. complete in all respect including cost of all necessary						
		fittings as required jointing materials and two coats of painting with approved paint in any position above ground. (Payment will be made on the centre line measurements of total pipe line including all specials.						
		No separate payment will be made for accesories, specials. Payment for painting will be made seperately)						
		(a) For Exposed Work PVC Pipes (Dia)						
		15mm	6.00	Mtr	101.00	Mtr		606.00
		25mm	3.00	Mtr	177.00 292.00	Mtr		531.00 876.00
		40 mm	3.00	Mtr	292.00	Mtr	6	9430.91
					Add 9%	for CGST		6248.78
						for SGST		6248.78
						al =		1928.48
					7.5	r L.W.Cess		819.28
						Total =	9	2747.70

RUPEES: EIGHTY-TWO THOUSAND SEVEN HUNDRED FORTY-EIGHT ONLY.

JE-III KPD

AE-II KPD

TERMS AND CONDITITON OF TENDERS

- All works to be carried out in a manner according to specification for original work now in laid as the regional works in building department circle.
- All materials, tools, plant and labour, the housing, water supply and transport will have to be provided by Contractor at their own cost inclusive of G.S.T. and other charges.
- 3. No extra work will be allowed without prior approval.
- 4. The contractors are requested to inspect the schedule of nature of works at site to save all eventualities connection with works any other information may be obtained from the OC, Buildings Office, Lalbazar. Any place of ignorance after submission of tender by the contractors will not be considered.
- 5. The quantities as shown against the item of work can be verified according to nature of works. Actual requirement to be done soon after containing the written approval of the Jt. CP(O), but contractors are liable for execution of varied quantities at their accepted rates. The rate of the addition item which are not found in the enclosed schedule will be based on building schedule of the regional works and buildings circle subject to approval of proper authority.
- The contractors should submit tender enclosed with Trade License, Income Tax return, GST, Credential, Under taking of black listed failure to which will be disqualified.
- 7. The work will be taken up within 07(Seven) days after receipt of work order, failing to which legal action may be taken against the firm.
- 8. The Commissioner of Police Kolkata reserves the right to reject any/or all the tender rates without assigning any reason and also to distribute the said works among the tenders. There is no guarantee that the lowest tender will be accepted by the authority concern.
- Tender addressed to the Commissioner of Police, Kolkata should be sent in a sealed cover super scribed name of tender to be dropped in the sealed TENDER BOX to be kept the OC, Buildings Office, LaLbazar at 18, Lalbazar Street, Kolkata-700 001 within 15.00 hrs on last date.
- 10. The Tender Committee will open the sealed tender in the Committee Room of Lalbazar, The Agencies may be present or send their authorized representative at the time of opening the sealed tender box.

C., Buildings(PHE)

PERCENTAGE RATE TENDER AND CONTRACT FOR WORKS: GENERAL RULES AND DIRECTIONS FOR THE GUIDANCE OF CONTRACTS.

1. All works proposed for execution by contract will be notified in a form of invitation of tender posted in public places and signed by the OC, Buildings Office, Lalbazar.

This form will state the work to be carried out, as well as the date of submitting and opening of tenders and the time allowed for carrying out the work, design and drawings and any other documents required in connection with work signed for the purpose of identification by the OC, Buildings Office, Lalbazar shall also be open for inspection by the contractor at the office of the OC, Building, Lalbazar during office hours.

- 2. In the event of the quotation being submitted by a firm, it must be signed separately by each member thereof or in the event of the absence of any partner it must be signed on his behalf by a person holding a power of attorney authorizing him to do so. Such power of attorney is to be produced with the tender and same in the case of a firm carried on by one member of a joint family, it must be disclose that the firm is duly registered under the Indian partnership Act.
- 3. Receipts for payment made on account of work, when executed by a firm, must also be signed by the several partners except where the contractors are described in their tender as a firm in which case the receipts must be signed in the name of the firm by one of the partners or by some other person having authority to give effectual receipts for the firm.
- 4. Any person who submits a tender shall fill up the usual printed form, stating at what rate he is willing to undertake each item of the work. Tenders which propose any alteration, in the work specified in the said form of invitation of tenders or in the time allowed for carrying out the work, or which contain any other conditions of any sort, will be liable to rejection. No single tender shall include more than one work but contractors who wish to quote for two or more works shall submit a separate tender for each. Tenders shall have the name and number of the work to which they refer written outside the envelope.
- 5 The Committee will open tenders in the presence of any intending contractors who may present at the time and will enter the amounts of the several tenders in a comparative statement in a suitable form.

The accepting authority reserves the right to reject any or all the tender without assigning any reasons and he will not be bound to accept either the lowest tender or any of the tenders.

, Buildings(PHE) Lalbazar.