Government of West Bengal Office of the Commissioner of Police 18, Lalbazar Street, Kolkata-700 001.

No. T-161/Gen/25-26

Date - 29. 07. 2025

NOTICE INVITING TENDER

Sealed tenders in printed form are invited for the following works from eligible tenderers as per particulars given below:

1. Name of work

Essential repairing and painting works in the office godown of O.C.

Buildings situated at 306, B. B. Ganguly Street, Kolkata.

(Details Estimate annexed)

2. Eligibility

All bonafide contractors /firms having experience / valid license for this

type of field.

3. Estimated Cost

: Rs. 65,922/-

Last date for submission of the tender

07. 08. 2025 up to, 15.00 hrs.

5. Time allowed for completion of works

10(ten) days after the issue of Work Order.

6. The intending tenderers may inspect the site on any working day during office time.

7. The intending tenderers will have to submit copy of valid Certificate of up to date Clearance of Trade License, Professional Tax, Income Tax, G.S.T and Credential along with tender papers for the work.

8. Sealed Tender addressed to The Commissioner of Police, 18, Lalbazar Street, Kolkata-700001 may be dropped in the box kept in front of the office of the Officer-in-Charge, Building Section, 2nd floor, Northern Building, 18, Lalbazar Street, Kolkata-700001 before the last date.

9. Sealed tender may also be sent by Registered Post / Speed Post superscribing the envelope as "Tender in response to Tender Notice No. T-161/Gen/25-26 dt. 29.07. 2025" so as to reach on or before the last date.

O.C. Buildings, Lalbazar, Kolkata.

Name of work: Repairing and painting works in the office Godown of O.C.Building situated at 306,B.B.Ganguly Street,Kolkata-700012 during the year 2025-2026

Reg. 15 Classing the concerte surface by renorming dirt and electric socializes and 9.50 vigitif 90.00 vig			2025-2026	Description of item			Pata	Unit	Amount
Page-45 Coloning the concrete surface by remarking dirth and details carefully deferred locations and 19 years of terrolling lives concrete by careful stripping with larms where in exposed, cutting the concrete to regular lifetime by careful stripping with larms where in exposed cutting the concrete to regular lifetime by careful stripping with the concrete with fresh concrete to regular lifetime by the concrete to regular lifetime of the displacement of the Regener in - Change of the concrete with fresh concrete to p. 50.0 square 309.00 square 190.00			Page & Item No		Qty	y Rate		Unit	
Degree 15 (1997)	1		Page-45	removing loose concrete by careful stripping untill hard surface is exposed, cutting the concrete to regular shape, wire brushing the exposed surface and removing debris from site	9.50	sqmtr	90.00	sqmtr	855.00
Page -10	2			be applied within manufacturer's specified time as per manufacturers specification. (0.4 kg / $\rm m^2$ of concrete surface). Note: Applicable only when the full diameter of reinforcement steel is	9.50	sqmtr	309.00	sqmtr .	2935.50
Page-45 Permit Pe	ž	3		wire netting, I.R.C. fabric mesh or X.P. M. fitted and fixed after typing the existing reinforcement on concrete without distributing the same and with proper scarping and cleaning the reinforcement and disturbed concrete with wire brush etc. after applying a coat of cement including the cost of wire netting I.R.C or X. P. M. & cost of all handling and scaffolding	9.50	sqmtr	522.00	sqmtr	4959.00
5 Page-15 1 Item-10 1 Item-11 1 Item-10 1 Item-10 1 Item-10 1 Item-10 1 Item-10 1 Item-10 1 Item-11 1 Item-10 1 Item-10 1 Item-10 1 Item-11 1 Item-10 1 Item-10 1 Item-11 1 Item-12 1 Item-12 1 Item-13 1 Item-13 1 Item-13 1 Item-14 1 Item-14 1 Item-14 1 Item-15 1 Item-15 1 Item-15 1 Item-15 1 Item-15 1 Item-16 1 Item-16 1 Item-16 1 Item-16 1 Item-16 1 Item-17 1 Item-16 1 Item-17 1 Item-17 1 Item-18 1 Item-18 1 Item-18 1 Item-18 1 Item-19 1 Item	4	1		coats of polymer based rust removing compound left for 24 hours, removing the coating and then applying two (2) coats of polymer modified anti corrosive protective coating formulated to	1,43	sqmtr	782.00	sqmtr ,	1114.35
tiem—5 adhesive and water profing properties by misring with water in proportion [1] bending agent water is a cement) as per Manufacturer's specification [Cement to be supplied by the Department] 7 Page-189 8 Page-189 9 Plaser to wail, floor, ceiling etc.] with sand and cement mortar including round of or chamlering correspond and common the control of the properties of the properties by misring out joints including throating, oosing and drip course, scalfolding/staging, where necessary (Found floor), [Excluding cost of chipping over concrete surface] 8 Page-45 8 Page-45 1 [tem-9] 9 Page-47 1 [tem-9] 9 Page-40 1 [tem-9] 2 [tem-9] 2 [tem-9] 3 [tem-9] 3 [tem-9] 4 [tem-9] 4 [tem-9] 4 [tem-9] 5 [tem-9] 5 [tem-9] 6 [tem-9] 6 [tem-9] 6 [tem-9] 6 [tem-9] 6 [tem-9] 7 [tem-10] 7 [tem-10] 8 [tem-9] 8 [tem-9] 9 [tem-10] 1 [tem-10] 2 [tem-10] 3 [tem-10] 4 [tem-10] 4 [tem-10] 4 [tem-10] 4 [tem-10] 5 [tem-10] 6 [tem-10] 6 [tem-10] 6 [tem-10] 6 [tem-10] 6 [tem-10] 6 [tem-10] 7 [tem-10] 7 [tem-10] 8 [tem-10] 8 [tem-10] 8 [tem-10] 8 [tem-10] 8 [tem-10] 9 [tem-10] 9 [tem-10] 9 [tem-10] 1 [tem-10]		5		Stripping off worn out plaster and raking out joints of walls, cellings etc. upto any height and in any floor including removing rubbish within a lead of $75m$ as directed.	15.50	sqmtr	19.00	sqmtı	294.50
tem-1 chamfering corners as directed and ruking out joints including throating, nosing and drip- course, sacificiting/staging where necessary (Forund floor); [Excluding cost of chipping over concrete surface] [i) With 1/s cement mortar.[c]-1/5 mm thick/plaster [ii] With 1/s cement mortar.[c]-1/5 mm thick/plaster [ii] With 1/s cement mortar.[c]-1/5 mm thick/plaster [iii] Page-195 [iii] Page-196 [iii] Removing old scales, bilaters etc. of interior surface of walls, ceiling by seraping etc. and preparing amooth and even surface with rendering, or cement mortar [1/2] (as necessary), to make the surface suitable for receiving distemper. [Payment against this tem will be made only when this has been done on the specific direction of the Engineer-in-changel. [iii] Page-196 [iii] Removing old scales, bilaters etc. of interior surface of walls, scaling with White Cement base water proof wall putty of preparing amount and (1.5 mm thick) [iii] Page-196 [iii] Page-196 [iii] Actyrilo Distemper to interior wall, ceiling with White Cement base water proof wall putty of provide make & brand (1.5 mm thick) [iii] Page-200 [iii] Page-200 [iii] Page-200 [iii] Page-200 [iii] Page-200 [iii] Page-200 [iii] Priming one coat on timber or plastered surface and thoroughly smoothening the protective coat of painting at the contact surface of the frame estuding coat of concrete, from but things and M.S. clamps. (The quantum should be corrected upon three decimals). [iii] Page-200 [iii] Priming one coat on timber or plastered surface with super gloss (iii) gloss). [iv] Two coats (with any shade except white) [iii] Page-200 [iii] Priming one coat on timber or plaster		6		adhesive and water proofing properties by mixing with water in proportion [1 bonding agent : 4 water : 6 cement) as per Manufacturer's specification [Cement to be supplied by the	15.50	sqmtr	88.00 *	sqmtr	1364.00
19 Page-15 Removing old scales, bilsters etc. of interior surface of walls.celling by seriphing etc. and properties around in the Spiaster with the content of the Spiaster of them 10 Page-198 Removing old scales, bilsters etc. of interior surface of walls.celling by seriphing etc. and properties around including eleming and since the same suitation with contact arts around the surface. It is sufficiently a surface with removing of some scales, bilsters etc. of interior surface of walls.celling by seriphing etc. and properties amount and even surface with rendering, or cement mortar (1:2) (as necessary), to make the same of walls and celling with White Cement base water proof wall putty of approved make & brand, (1.5 mm thick) 11 Page-198 Rendering the Surface of walls and celling with 'na coat of solvent based interior grade acrytic former to primer transport of the surface of the frame estuding cost of concrete, from bilt Hings and M.S clamps. (The quantum should be corrected upto three decimals). 12 Page-196 Wood work in door and window frame litted and fixed in position complete including a protective coat of painting at the contact surface of the frame estuding cost of concrete, from bilt Hings and M.S clamps. (The quantum should be corrected upto three decimals). 14 Page-203 Removing loose scales, bilsters etc. from old painted surface and thoroughly smoothening the surface to make the same suitable for receiving fresh coat of painting and monothening surface by sand papering etc. 15 Page-200 (a) Priming one coat on timber or plastered surface with synthetic oil bound pomer of tem-1 approved quality including smoothening surfaces by sand papering etc. 16 Page-200 (b) Painting with best quality synthetic enamel paint of approved make and brand including the surface. (The coessary (a) On timber or plastered surface with super gloss (hi gloss) (iv) Two coats (with any shade except white) 17 Page-200 (c) Page-200 (d) Painting surfaces by sand papering etc. including using of appro		7		chamfering corners as directed and raking out joints including throating, nosing and drip course, scaffolding/staging where necessary (Ground floor). [Excluding cost of chipping over					
Page-198 Removing old seales, bilisters etc. of interior surface of walls, celling by seraping etc. and preparing smooth and even surface with rendering, or cement mortrat (1:2) (as necessary), to make the surface suitable for receiving dislemper. [Payment against this item will be made only when this has been done on the specific direction of the Engineer-in-charge]. Page-198 Removing old seales, bilisters etc. of interior surface of walls, celling by seraping etc. and preparing smooth and even surface with rendering, or cement mortrat (1:2) (as necessary), to make the surface suitable for receiving dislemper. [Payment against this item will be made only when this has been done on the specific direction of the Engineer-in-charge]. Page-198 Rendering the Surface of walls and celling with White Cement base water proof wall putty of tem-10 primer (as) per manufacturer's specification; including cleaning and smoothning of surface. Two Coats Page-196 Arrytic Distemper to interior wall, celling with: a coat of solvent based interior grade acrylic primer (as) per manufacturer's specification; including cleaning and smoothning of surface. Two Coats Page-114 Wood work in door and window frame fitted and fixed in position complete including a protective coat of painting at the contact surface of the frame existing cost of concrete, from but Hinges and Mis-clamps. (The quantum should be corrected upon three decimals). Page-200 Removing loose scales, blisters etc. from old painted surface and thoroughly smoothening the surface to make the same suitable for receiving fresh coat of paint Page-200 Removing loose scales, blisters etc. from old painted surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Apperlate Page-200 Removing loose scales, blisters etc. from old painted surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Apperlate Page-200 Removing loose s				(ii) With 1:4 cement mortar.(c) 10 mm thick plaster	9.50	sqmtr	133.00	sqmtr	2340.57 1263.56
7 Page-198 Removing old scales, blisters etc. of interior surface of walls.ceiling by scraping etc. and preparing amoth and even surface with rendering, or cement mortar (1:2) (as necessary), to make the surface suitable for receiving distemper. (Payment against this item will be made only when this has been done on the specified direction of the Engineer-in-charge). 11 Page-198 Rendering the Surface of walls and celling with White Cement base water proof wall putty of approved make & brand (1.5 mm thick) 12 Page-198 Arcylic Distemper to interior wall, celling with white Dement base water proof wall putty of primer (as per manufacturer's specification) including cleaning and smoothning of surface. Two Coats 13 Page-114 Wood work in door and window frame litted and fixed in position complete including a protective coat of painting at the contact surface of the frame extuding cost of concrete, from Butt Hinges and M.S clamps. (The quantum should be corrected upon three decimals). 14 Page-203 Removing loose scales, blisters etc. from old painted surface and thoroughly smoothening the surface to make the same suitable for receiving fresh coat of paint. 15 Page-200 (a) Priming one coat on timber or plastered surface with synthetic oil bound primer of least of the surface by sand papering etc. 16 Page-200 (A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. 16 Page-200 (A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. 17 Page-18 Rendering surface by sand papering etc. including using of approved patity etc. on the surface, if necessary (id) On timber or plastered surface. With super gloss (hi-gloss) -tivi Two coats (with any shade except white) 18 Page-200 (A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. Including using of approved put two coats (with any shade exce		8		at manufacturer's specified rate) for concrete of various grades.					
ltem-4 preparing smooth and even surface with rendering, or cement mortar (1:2) [as necessary), to make the surface suitable for receiving distemper. [Payment against this item will be made only when this has been done on the specific direction of the Engineer—charge). 11 Page-198 Rendering the Surface of walls and ceiling with White Cement base water proof wall putty of approved make & brand. (1.5 mm thick) 12 Page-196 Acrylic Distemper to interior wall, ceiling with a coat of solvent based interior grade acrylic primer (as per manufacturer's specification) including cleaning and smoothning of surface. Two Coats 13 Page-114 Wood work in door and window frame fitted and fixed in position complete including a protective coat of painting at the contact surface of the frame exituding cost of concrete, Iron Butt Hinges and M.S clamps. (The quantum should be corrected upto three decimals). 14 Page-203 Removing loose scales, blisters etc. from old painted surface and thoroughly smoothening the surface to make the same sultable for receiving fresh coat of paint. 15 Page-200 [a) Priming one coat on timber or plastered surface with synthetic oil bound pomer of lem-1 approved quality including smoothening surfaces by sand papering etc. 16 Page-200 [A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved patty etc. on the surface, if necessary, 1(a) On timber or plastered surface: With super gloss [higloss] - [wi] Total Scales. Grand Total 65269.66 Add 1% L.W.Cess G625.7. 25313.24 2629.66 273 Add 9% for C.G.S.T. 4978.15 274 Total 65269.66 275 Grand Total 65922.38		9		Ordinary Cement concrete (mix 1:2:4) with graded stone chips (6mm nominal size) excluding shuttering and reinforcement, if any, in gound floor as per relevant IS codes. Pakur variety	3.23	cum	3449.00	cum	17703.43
lem-1 spec-198 Rendering the Surface of walls and ceiting with white Cement base water pitot wan puty of lem-1 specified from thick) 12 Page-196 Marylic Distemper to interior wall, ceiling with a coat of solvent based interior grade acrylic primer (as per manufacturer's specification) including cleaning and smoothning of surface. Two Coats 13 Page-114 Wood work in door and window frame litted and fixed in position complete including a protective coat of painting at the contact surface of the frame excluding cost of concrete, from Butt Hinges and M.S clamps. (The quantum should be corrected upto three decimals). 14 Page-203 Removing loose scales, blisters etc. from old painted surface and thoroughly smoothening the surface to make the same suitable for receiving fresh coat of paint 15 Page-200 Item-1 (a) Priming one coat on timber or plastered surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. 16 Page-200 Item-2 (A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary (a) On timber or plastered surface: With super gloss (hi-gloss) - (iv) Two coats (with any shade except white) 15 Page-200 Add 9% for C.G.S.T. 4978.11 Add 9% for S.G.S.T. 4978.11 Add 9% for S.G.S.T. 4978.11 Add 9% for C.G.S.T. 4978.11 Add 9% fo	1	10		preparing smooth and even surface with rendering or cement mortar (1:2) [as necessary], to make the surface suitable for receiving distemper. (Payment against this item will be made only	195.50	sqmtr	10.17	sqmtr .	1988.24
ltem-10 primer (as per manufacturer's specification) including cleaning and smoothning of surface. Two Coats 13 Page-114 Wood work in door and window frame fitted and fixed in position complete including a protective coat of painting at the contact surface of the frame extuding cost of concrete, from Butt Hinges and M.S clamps. (The quantum should be correted upto three decimals). 14 Page-203 Removing loose scales, blisters etc. from old painted surface and thoroughly smoothening the surface to make the same suitable for receiving fresh coat of paint. 15 Page-200 Item-1 (a) Priming one coat on timber or plastered surface with synthetic oil bound pomer of approved quality including smoothening surface by sand papering etc. 16 Page-200 Item-2 (A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary: (a) On timber or plastered surface: With super gloss (hi-gloss) - (iv) Two coats (with any shade except white) 15 Page-200 Add 9% for C.G.S.T. 4978.11 Add 9% for C.G.S.T. 4		11		approved make & brand.(1.5 mm thick)		squitr			3214.70
Page-114 Wood work in door and window hather after the farm passed of Congrete, from protective coal of paintifies at the contact surface of the frame exiding cost of concrete, from Butt Hinges and M.S clamps. (The quantum should be corrected upto three decimals). Removing loose scales, blisters etc. from old painted surface and thoroughly smoothening the surface to make the same suitable for receiving fresh coat of paint. Page-203 [a] Priming one coat on timber or plastered surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Agence 104 [a] Priming one coat on timber or plastered surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. [b] Page-200 [a] Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary (a) On timber or plastered surface : With super gloss (hi-gloss) (iv) Two coats (with any shade except white) Add 9% for C.G.S.T. Add 9% for S.G.S.T. 4978.1: Total Add 9% for S.G.S.T. 4978.1: Total 65269.64 Add 1% L.W.Cess Grand Total 65922.33		12		primer (as per manufacturer's specification) including cleaning and smoothning of surface. Two	195.50	sqmtr	70.00	sqmtr	13685.00
Removing loose scales, blisters etc. from oid painted surface and thoroughly smoothering the surface to make the same suitable for receiving fresh coat of paint 15 Page-200 [a] Priming one coat on timber or plastered surface with synthetic oil bound primer of approved quality including smoothering surfaces by sand papering etc. 16 Page-200 [A] Painting with best quality synthetic enamel paint of approved make and brand including smoothering surface by sand papering etc. including using of approved putty etc. on the surface, if necessary (a) On timber or plastered surface (With super gloss (hi-gloss) (iv) Two coats (with any shade except white) 55313.21 Add 9% for S.G.S.T. 4978.11 Total 65269.61 Add 1% L.W.Cess 652.76 Grand Total 65922.33		13		protective coat of painting at the contact surface of the frame extuding cost of concrete, from		cum	98112.00	cum	1962.24
ltem-1 approved quality including smoothening surfaces by sand papering etc. 16 Page-200 (A) Painting with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary (a) On timber or plastered surface :With super gloss (hi gloss) -(iv) Two coats (with any shade except white) Add 9% for C.G.S.T. Add 9% for C.G.S.T. 4978.1' Total 65269.6' Add 1% L.W.Cess Grand Total 65922.3'		14		Removing loose scales, blisters etc. from old painted surface and thoroughly smoothening the surface to make the same suitable for receiving fresh coat of paint	9.50	sqmtr	21.00	sqmtr	199.50
Page-200 All Painting with best quality synthetic ename paint of approved putty etc. on the surface, if necessary (a) On timber or plastered surface :With super gloss (hi-gloss) (iv) Two coats (with any shade except white) Add 9% for C.G.S.T. 4978.1		15		(a) Priming one coat on timber or plastered surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc.	9.50	sqmtr	38.00	sqmtr	361.00
Add 9% for C.G.S.T. 4978.19 Add 9% for S.G.S.T. 4978.19 Total 65269.66 Add 1% L.W.Cess 652.76 Grand Total 65922.36		16	900	smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary (a) On timber or plastered surface :With super gloss (hi-gloss) -(iv) Two		sqmtr	81.00	sqmtr	769.50
							Add 9% f To Add 1% Gran	or S.G.S.T. otal L.W.Cess d Total	55313.28 4978.19 4978.19 65269.66 652.70 65922.36 65922.00

(Rupees Sixty Five Thousand Nine Hundred and Twenty Two Only)

Jah ze od

Koikasa Police Directorate Govi, of West Bengal

TERMS AND CONDITITON OF TENDERS

- 1. All works to be carried out in a manner according to specification for original work now in laid as the regional works in building department circle.
- 2. All materials, tools, plant and labour, the housing, water supply and transport will have to be provided by Contractor at their own cost inclusive of G.S.T. and other charges.
- 3. No extra work will be allowed without prior approval.
- 4. The contractors are requested to inspect the schedule of nature of works at site to save all eventualities connection with works any other information may be obtained from the OC, Buildings Office, Lalbazar. Any place of ignorance after submission of tender by the contractors will not be considered.
- 5. The quantities as shown against the item of work can be verified according to nature of works. Actual requirement to be done soon after containing the written approval of the Jt. CP(O), but contractors are liable for execution of varied quantities at their accepted rates. The rate of the addition item which are not found in the enclosed schedule will be based on building schedule of the regional works and buildings circle subject to approval of proper authority.
- 6. The contractors should submit tender enclosed with Trade License, Income Tax return, GST, Credential, Under taking of black listed failure to which will be disqualified.
- 7. The work will be taken up within 07(Seven) days after receipt of work order, failing to which legal action may be taken against the firm.
- 8. The Commissioner of Police Kolkata reserves the right to reject any/or all the tender rates without assigning any reason and also to distribute the said works among the tenders. There is no guarantee that the lowest tender will be accepted by the authority concern.
- 9. Tender addressed to the Commissioner of Police, Kolkata should be sent in a sealed cover super scribed name of tender to be dropped in the sealed TENDER BOX to be kept the OC, Buildings Office, LaLbazar at 18, Lalbazar Street, Kolkata-700 001 within 15.00 hrs on last date.
- 10. The Tender Committee will open the sealed tender in the Committee Room of Lalbazar, The Agencies may be present or send their authorized representative at the time of opening the sealed tender box.

O.C., Buildings, Lalbazar.

PERCENTAGE RATE TENDER AND CONTRACT FOR WORKS: GENERAL RULES AND DIRECTIONS FOR THE GUIDANCE OF CONTRACTS.

1. All works proposed for execution by contract will be notified in a form of invitation of tender posted in public places and signed by the OC, Buildings Office, Lalbazar.

This form will state the work to be carried out, as well as the date of submitting and opening of tenders and the time allowed for carrying out the work, design and drawings and any other documents required in connection with work signed for the purpose of identification by the OC, Buildings Office, Lalbazar shall also be open for inspection by the contractor at the office of the OC, Building, Lalbazar during office hours.

- 2. In the event of the quotation being submitted by a firm, it must be signed separately by each member thereof or in the event of the absence of any partner it must be signed on his behalf by a person holding a power of attorney authorizing him to do so. Such power of attorney is to be produced with the tender and same in the case of a firm carried on by one member of a joint family, it must be disclose that the firm is duly registered under the Indian partnership Act.
- 3. Receipts for payment made on account of work, when executed by a firm, must also be signed by the several partners except where the contractors are described in their tender as a firm in which case the receipts must be signed in the name of the firm by one of the partners or by some other person having authority to give effectual receipts for the firm.
- 4. Any person who submits a tender shall fill up the usual printed form, stating at what rate he is willing to undertake each item of the work. Tenders which propose any alteration, in the work specified in the said form of invitation of tenders or in the time allowed for carrying out the work, or which contain any other conditions of any sort, will be liable to rejection. No single tender shall include more than one work but contractors who wish to quote for two or more works shall submit a separate tender for each. Tenders shall have the name and number of the work to which they refer written outside the envelope.
- 5 The Committee will open tenders in the presence of any intending contractors who may present at the time and will enter the amounts of the several tenders in a comparative statement in a suitable form.
- The accepting authority reserves the right to reject any or all the tender without assigning any reasons and he will not be bound to accept either the lowest tender or any of the tenders.

O.C., Buildings, Lalbazar.